



PennEngineering

Corporate Headquarters – Danboro, PA

5190 Old Easton Rd.

Danboro, PA 18916

Phone: 215-766-8853

Toll-Free Phone: 1-800-237-4736 (U.S. only)

Email: info@pemnet.com

Website: www.pemnet.com

Part # LAS-M4-2MD, Floating self-clinching, locking thread fasteners LA4, LAC, LAS - Metric


Locking and Non-locking Threads

These fasteners provide load-bearing threads in thin sheets and permit up to 0.76mm adjustment for mating hole misalignment.

The self-clinching feature offers fast and simple assembly. The fasteners are squeezed into prepared holes using any standard press. The sheet remains flush on one side, and the fastener is permanently locked in place.

Extra strength and support in assembly is obtained by the threads of the floating nut extending fully into the retainer

[+ more](#)




Specifications



Thread Size x Pitch M4 x 0.7


Thread Type Self-Locking



Thread Code M4

Shank Code 2

A (Shank) Max. 1.38 mm



Min. Sheet Thickness 1.38 mm

Hole Size in Sheet + 0.08 9.35 mm

C Max.	9.33 mm
D Max.	9.28 mm
E ± 0.38	11.18 mm
T2 Max.	5.34 mm
Min. Dist. Hole C/L to Edge	8.64 mm
Float	0.38mm minimum, in all directions from center, 0.76mm total
Fastener Material	Steel
Fastener Materials - Retainer	Heat-Treated Carbon Steel
Fastener Materials - Nut	300 Series Stainless Steel
Retainer Finish	Zinc plated per ASTM B633, SC1 (5µm), Type III, colorless
Nut Finish	Black Dry-film Lubricant
For Use in Sheet Hardness¹	HRB 70 / HB 125 or Less
Thread Specification	Internal, B1.13M, 6H ANSI/ASME
CAD Supplier	PennEngineering® (PEM®)

¹ HRB - Hardness Rockwell “B” Scale. HB - Hardness Brinell.